ISU KLM Meeting

November 22, 2023

SBC Interface

Progress

Progress

- Local ethernet network created with static IP addresses

Progress

- Local ethernet network created with static IP addresses
  - Network consists of 2 Raspberry Pis, one Rocky Linux computer, and two ethernet switches
    - Switch 1: Pi #1 and bridge to Switch 2
    - Switch 2: Computer, Pi #2, and bridge to Switch 1

Progress

- Local ethernet network created with static IP addresses
  - Network consists of 2 Raspberry Pis, one Rocky Linux computer, and two ethernet switches
    - Switch 1: Pi #1 and bridge to Switch 2
    - Switch 2: Computer, Pi #2, and bridge to Switch 1
  - ssh key pairs created, copied, and working (type “ssh pi1”)

Progress

- Local ethernet network created with static IP addresses
  - Network consists of 2 Raspberry Pis, one Rocky Linux computer, and two ethernet switches
    - Switch 1: Pi #1 and bridge to Switch 2
    - Switch 2: Computer, Pi #2, and bridge to Switch 1
  - ssh key pairs created, copied, and working (type “ssh pi1”)
  - scp speeds:
    - 3 MB file: 0.375 s upload and download, consistently (~20 trials)

Progress

- Local ethernet network created with static IP addresses
  - Network consists of 2 Raspberry Pis, one Rocky Linux computer, and two ethernet switches
    - Switch 1: Pi #1 and bridge to Switch 2
    - Switch 2: Computer, Pi #2, and bridge to Switch 1
  - ssh key pairs created, copied, and working (type “ssh pi1”)
  - scp speeds:
    - 3 MB file: 0.375 s upload and download, consistently (~20 trials)
    - 10 MB file: 1 s upload, 1.2 s download, consistently (~20 trials)

Progress

- Local ethernet network created with static IP addresses
  - Network consists of 2 Raspberry Pis, one Rocky Linux computer, and two ethernet switches
    - Switch 1: Pi #1 and bridge to Switch 2
    - Switch 2: Computer, Pi #2, and bridge to Switch 1
  - ssh key pairs created, copied, and working (type “ssh pi1”)
  - scp speeds:
    - 3 MB file: 0.375 s upload and download, consistently (~20 trials)
    - 10 MB file: 1 s upload, 1.2 s download, consistently (~20 trials)
    - 100 MB file: 10 s upload, 9.1 s download, consistently (~10 trials)

Progress

- Local ethernet network created with static IP addresses
  - Network consists of 2 Raspberry Pis, one Rocky Linux computer, and two ethernet switches
    - Switch 1: Pi #1 and bridge to Switch 2
    - Switch 2: Computer, Pi #2, and bridge to Switch 1
  - ssh key pairs created, copied, and working (type “ssh pi1”)
  - scp speeds:
    - 3 MB file: 0.375 s upload and download, consistently (~20 trials)
    - 10 MB file: 1 s upload, 1.2 s download, consistently (~20 trials)
    - 100 MB file: 10 s upload, 9.1 s download, consistently (~10 trials)
    - Consistent across 2 orders of magnitude: ~ 5-10 MB/s upload, ~ 8-11 MB/s download

Progress

- Local ethernet network created with static IP addresses
  - Network consists of 2 Raspberry Pis, one Rocky Linux computer, and two ethernet switches
    - Switch 1: Pi #1 and bridge to Switch 2
    - Switch 2: Computer, Pi #2, and bridge to Switch 1
  - ssh key pairs created, copied, and working (type “ssh pi1”)
  - scp speeds:
    - 3 MB file: 0.375 s upload and download, consistently (~20 trials)
    - 10 MB file: 1 s upload, 1.2 s download, consistently (~20 trials)
    - 100 MB file: 10 s upload, 9.1 s download, consistently (~10 trials)
    - Consistent across 2 orders of magnitude: ~ 5-10 MB/s upload, ~ 8-11 MB/s download
    - Files are simple text files and speed test is from someone’s github page

To Do

To Do

- Create bash script to periodically pull files from the Pis

To Do

- Create bash script to periodically pull files from the Pis
- Create bash script to periodically clean up Pis (with period >> pull period)

To Do

- Create bash script to periodically pull files from the Pis
- Create bash script to periodically clean up Pis (with clean period >> pull period)
- Write documentation in a formal way to reproduce the procedure at KEK

To Do

- Create bash script to periodically pull files from the Pis
- Create bash script to periodically clean up Pis (with period >> pull period)
- Write documentation in a formal way to reproduce the procedure at KEK
- Talk with Avinash about exceptions and failures that could occur while pulling files from the Pis and how to communicate such situations